

essential

AutoChlor[®]

Classic[™] Mark II



The tried and trusted classic for over 25 years

AIS
WATER
Enhancing life

AutoChlor® Classic™ Mark II

SALINITY RANGE: 3,500PPM – 5,500PPM

First introduced over 25 years ago, **AutoChlor® Classic™** series is the most popular of AIS' product range, and is renowned for its simplicity, reliability and easy installation.

All models in the Classic™ series have been progressively perfected and **AutoChlor® Classic™ Mark II** now features an aluminium heatsink for even greater resilience in high temperature locations and conditions. The **AutoChlor® Classic™ Mark II** provides pool owners with practicality and peace of mind when it comes to pool water disinfection.

Warranty:

AutoChlor® Classic™ is covered by a **four (4) year warranty on power supply and electrolytic cell for residential use and one (1) year warranty for commercial applications.**



Specifications

MODELS	CHLORINE OUTPUT	INPUT AC POWER CONSUMPTION	INPUT CURRENT	OUTPUT CURRENT	WATER FLOW	DIMENSION (PACKAGED)	WEIGHT (PACKAGED)	DIMENSION (POWER SUPPLY)	APPROXIMATE POOL SIZE
	g/hr	Kilowatt hour (kWh)	Amps (A)	Amps (A)	L/min	L x W x H (cm)	kg	L x W x H (cm)	m ³
RP15	15	0.153	0.82	15	150-450	38x34x27	11.5	36.2x18.5x22.1	30
RP20*	20	0.227	1.00	20		38x34x27	13.5	36.2x18.5x22.1	40
RP25*	25	0.253	1.06	16		38x34x27	13.5	36.2x18.5x22.1	50
RP35 (LS Only)	35	0.505	1.65	30		43x33x27	20.5	41.3x20.2x25.7	70
RP36	36	0.234	1.08	20		38x34x27	13.5	36.2x18.5x22.1	70
RP50 (HD Only)	50	0.388	1.85	50		43x33x27	20.5	41.3x20.2x25.7	100
RP64 (HD Only)	64	0.525	2.70	35		43x33x27	20.5	41.3x20.2x25.7	120
RP80 (HD Only)	80	0.672	2.80	45		43x33x27	21	41.3x20.2x25.7	160

*Low salt 3,000ppm (LS) Model available
All tests were conducted at the temperature of 26°C, pH 7.7, salinity level 5,000ppm and flow rate 200L/m

AutoChlor® Classic™ Mark II features:

- **Wide Chlorine Output Range** from 15g/hr to 80g/hr
- **Powder-Coated Steel Construction** - delivering a durable and corrosion resistant enclosure
- **External Aluminium Heatsink** - providing enhanced cooling to alleviate internal heat
- **Robust and Reliable Transformer** - resistant to power fluctuations and high temperatures
- **Tinted Polycarbonate Front Cover** - protecting against direct sunlight and accidental splashes
- **Simplified User Interface** - retaining only essential control functions
- **Standard Safety Measures** - preventing damage caused by overloading, water flow interruption, high/low salt and other unforeseen events
- **Reverse Polarity (RP) Function** - reduces calcium build-up on electrodes, resulting in less maintenance
- **Genuine AIS Anode** - ensuring the longevity of the electrolytic cell
- **Proudly Australian Designed and Manufactured**

Optional Extras:

- **Heavy Duty Anode** – delivering longer cell lifespan and comes with an 18 month commercial warranty (RP50, RP64 & RP80)
- **Digital Backup Timer** - ensuring chlorine production resumes at pre-set times after power outages
- **Low Salt Model** – enabling operation in low salinity pool water (3000ppm)
- **Pool Light Transformer** - providing 12v, 24v or 36v timed power output

© Australian Innovative Systems Pty Ltd t/a AIS Water. AIS Water reserves the right to discontinue or change any of the products, styles, colours, specifications, performance characteristics, materials, services or other details referred to herein at any time without notice. Images and graphics are indicative and are for illustration purposes only.

51 Millennium Place,
Tingalpa, QLD 4173 Australia



info@aiswater.com.au



+61 7 3396 5222

aiswater.com



Scan any AIS Water logo to learn "Why choose AIS?"

AIS

WATER
Enhancing life